

SH-155 Polysiloxane Resin

Description

SH-155 is a thermosetting alcohol soluble silicone polymer resin with the characteristics of single component non curing, good temperature resistance, flexibility, and can be used as a ceramic primer.

◆ High temperature resistance

◆ Flexibility

Application

- ✓ As a ceramic primer
 - ✓ As a resin modifier, used to introduce organosilicon components into other resins
-

Product Index

Appearance:	Transparent to translucent liquid
Solid content:	40.00±2.00%
Specific Gravity:	1.00-1.20
Viscosity:	<100cp
PH:	2.00-4.00

Method of application:

Before coating the product, the substrate needs to be cleaned to remove surface grease, dust, etc. It is recommended to sandblasting or other surface treatment methods on the substrate surface to ensure the best adhesion of the coating on the substrate. Suggested spraying conditions: dry and wet spraying; Suggested drying conditions: temperature $\geq 80\text{ }^{\circ}\text{C}$, time 6min-10min.

Storage

Store in a sealed,dark,cool,ventilated,and dry environment,with a shelf life of 6 months(unopened).

Packing

25kg/drum; 200kg/drum

Discharge

Do not discharge it into the wastewater system, put it in a specific container

for professional treatment.

Emergency treatment

1. If there is a leak or overflow, please collect it in a container and clean the ground pollutants with a cloth.
2. If this product accidentally gets into the eyes, immediately rinse with plenty of water for at least 15 minutes. If you feel pain, please seek medical attention immediately.
3. If this product comes into contact with the skin, please wash it with water and soap. Seek medical attention immediately if feeling unwell.
4. If you accidentally inhale spray or gas in the oven, immediately transfer to a fresh air place, and then seek medical advice.

Updated date: 2025.01.09